


ANDALUSI



Model: ANDALUSI
 Size: 28X33 cm
 Thickness: 10 mm
 Material: PORCELANIC TILE

| Technical Features | | Referencial Normative |
|---|---|---------------------------|
| Manufacture Process | Single Fired Tiles | Dry Pressing ceramic tile |
| Thickness (mm.) | 10 | UNE EN ISO 10545 Part 2 |
| Length. Width , density, straightness, flatness. | Fulfills the requirements applied to each model defined in the normative UNE-EN-14411 for Group Bla | UNE EN ISO 10545 Part 2 |
| Water absorption | E<0.5 % | UNE EN ISO 10545 Part 3 |
| Resistance to flexion (N/mm.2) and breaking strength (N) | >35 >1300 | UNE EN ISO 10545 Part 4 |
| Resistance to superficial abrasion (Glazed Tiles) | 4 | UNE EN ISO 10545 Part 7 |
| Resistance to scratch (Mohs) | 5 | UNE EN ISO 10545 Part 8 |
| Resistance to termal clash | Resists Test | UNE EN ISO 10545 Part 9 |
| Resistance to crack | Resists Test | UNE EN ISO 10545 Part 11 |
| Frost Resistance | Resists Test | UNE EN ISO 10545 Part 12 |
| Anti-slip | Class 1 | UNE ENV 12633:2003 |

| Chemical Resistance | | |
|--|---------|--------------------------|
| Domestic cleaning products | GA | UNE EN ISO 10545 Part 13 |
| Swimming Pool Salt | GA | |
| Acids and bases (low concentration) | GLA/GHA | |
| Resistance to stains | Class 5 | UNE EN ISO 10545 Part 14 |

Documentation with commercial information. It cannot be used for administrative nor judicial purposes without Realonda S.A authorization.

Colors of this piece on this technical card are illustrative and can differ from the real piece.